



Specification : EN10253-1
Material : S235

Diam. Jashtëm. × Trashësia	
Ext. Diam. × Thickness	
mm × mm	
21.3 × 2.0	21.3 × 2.0
26.9 × 2.3	26.9 × 2.3
30.0 × 2.6	30.0 × 2.6
33.7 × 2.6	33.7 × 2.6
38.0 × 2.6	38.0 × 2.6
42.4 × 2.6	42.4 × 2.6
44.5 × 2.6	44.5 × 2.6
48.3 × 2.6	48.3 × 2.6
60.3 × 2.9	60.3 × 2.9
70.0 × 2.9	70.0 × 2.9
76.1 × 2.9	76.1 × 2.9
88.9 × 3.2	88.9 × 3.2
101.6 × 3.6	101.6 × 3.6
108.0 × 3.6	108.0 × 3.6
114.3 × 3.6	114.3 × 3.6
127.0 × 4.0	127.0 × 4.0
133.0 × 4.0	133.0 × 4.0
139.7 × 4.0	139.7 × 4.0
159.0 × 4.5	159.0 × 4.5
168.3 × 4.5	168.3 × 4.5
193.7 × 5.6	193.7 × 5.6
219.1 × 6.3	219.1 × 6.3
244.5 × 6.3	244.5 × 6.3
273.0 × 6.3	273.0 × 6.3
323.9 × 7.1	323.9 × 7.1

SEAMLESS CARBON STEEL WELDING FITTINGS

Specification : ANSI B16.9
Material : ASTM A234 WPB



		Caps -Kapak		Tees - Tāv			
		SCH STD (≤ 10" SCH40)		SCH STD (≤ 10" SCH40)	SCH XS (≤ 8" SCH80)		
		Trashēsia	Lartēsia	Pesha	Pesha	Trashēsia	Pesha
		Thick-ness	Height	Weight	Weight	Thick-ness	Weight
Pērmasat	Diam. Jashtēm	T	E	kg	kg	T	kg
Size	Ext.Dia. mm	mm	mm			mm	
1/2"	21	2.77	25	0.04	0.08	3.73	0.1
3/4"	27	2.87	25	0.05	0.11	3.91	0.14
1"	33	3.38	38	0.11	0.24	4.55	0.31
1.1/4"	42	4	38	0.14	0.41	4.85	0.54
1.1/2"	48	4	38	0.17	0.6	5.08	0.8
2"	60	3.91	38	0.23	0.87	5.54	1.2
2.1 / 2"	73	5.16	38	0.39	1.66	7.01	2.19
3"	89	5	51	0.66	1.9	7.62	2.57
3.1/2"	102	5.74			2.62		
4"	114	6.02	64	1.17	4.13	8.56	5.74

5"	141	6.55	76	1.91	6.55	9.53	9.3
6"	168	7.11	89	2.9	9.73	10.97	14.7
8"	219	8.18	102	5.19	18	12.7	27.4
10"	273	9.27	127	9.15	30.8		
12"	324	9.53	152	13.3	44.3		
14"	356	9.53	165	15.9	53.7		
16"	406	9.53	178	20	66.3		
18"	457	9.53	203	25.6	84.1		
20"	508	9.53	229	31.9	104		